

HDS 8/18-4 MX (1.077-652.0)



Osnovni podaci

- Eko tehnologija, turbo ventilacija, nova tehnologija gorionika, precizna regulacija hemije
- Centralna komandna konzola, 25 lit. rezervoar za gorivo, kompletan monitoring sredstva po rezervoarima
- Nova usavršena 3-klipna aksijalna pumpa sa vecom efikasnošću, keramički klipovi, integrisani kotur sa niskim trenjem i 20 met. creva vis. pritiska
- Laka za transport viljuškaram, veliki gumirani točkovi sa kočnicama
- Šasija otporna na koroziju, otpor dimnjaka od prohroma, senzor izduvnih gasova

Standardna oprema



20 m visokopritisno crevo, NW 8, 400 bar sa AVS sistemom (LONGLIFE)



Easy-Press pištolj sa regulacijom pritiska



Prohromska cev (1050 mm)



Power mlaznica (25°)



Mlaznica za paru

Tehnički podaci

• Priključni napon	400 V / 3 ~ / 50 Hz
• Protok vode	400 - 800 l/h
• Radni pritisak	30-180 bar / 3-18 MPa
• Snaga motora	5,5 kW
• Max. temp. vode.	155/80 C
• Težina	163 kg

2250 Eura
+PDV

keller doo
018/274-030